BERNSTEIN Series CT plastic enclosures are manufactured from high-grade polycarbonate or ABS. They are particularly suitable for encapsulating electrical and electronic components as well as complete small-scale controllers. All enclosures are available with a transparent polycarbonate cover. The enclosures correspond to protection class IP 65 in accordance with DIN EN 60529.

Attachment bosses are provided on the base of the plastic enclosures for mounting built-in components. The components can be simply secured with the self-tapping mounting screws that come with the enclosure. With their attachment bosses in the base, BERNSTEIN plastic enclosures offer many direct mounting options. Mounting rails can be installed without mounting plates on the central bosses.

BERNSTEIN Series CT enclosures are supplied as standard with the quick-release fastener developed and patented by BERNSTEIN. The quick-release fasteners that come with the enclosure are simply pressed and locked into the holes in the cover. They are made from stainless steel. The protection class (on the standard enclosure) is ensured by a factory-fitted seal. BERNSTEIN polycarbonate and ABS enclosures are produced as standard in the colour RAL 7035 (light grey). On account of its material properties, the polycarbonate version offers specific advantages in terms of impact strength, UV resistance and operating temperature range. Thanks to the many attachment bosses in the body, both versions provide many direct mounting options.

Technical data

Material

Polycarbonate, transparent polycarbonate or ABS

Seal

Foamed PUR seal Neoprene (CR) round cord (silicone-free) Silicone round cord

Quick-release fastener

Stainless steel, self-locking, cross recessed head

Optionally:

Stainless steel cover screw, cross recessed head Sealed cover screws, galvanised steel, (9 S 20 K), slot head


Coloui

RAL 7035 (light grey)

Other colours (dyeing) for large quantities available on request

Temperature range of CT enclosures

- -40°C to +120°C (Polycarbonate)
- -40°C to +80°C (ABS)



Temperature range of seals

Standard:

-40°C to +100°C (PUR seal)

Optionally:

- -30°C to +80°C (Neoprene seal)
- -60°C to +130°C (silicone seal)

Protection class

IP 65

Approbations

(Label on demand)

c UL us (polycarbonate enclosures)

c CSA us (polycarbonate enclosures)



					Polycarbonate e	nclosure	Polycarbonate er transparent cove		ABS enclosure		ABS enclosure w transparent cove	
Dime	ensio	ns/mr	n		Article number	Туре	Article number	Туре	Article number	Туре	Article number	Туре
L	х	В	х	Н								
52	Х	50	Х	35	2500000000	CT-501	2501000000	CT-501 T	3500000000	CT-502	3501000000	CT-502 T
65	Х	50	Х	35	2520000000	CT-521	2521000000	CT-521 T	3520000000	CT-522	3521000000	CT-522 T
82	Х	80	Х	55	2540000000	CT-541	2541000000	CT-541 T	3540000000	CT-542	3541000000	CT-542 T
82	Х	80	Х	85	2560000000	CT-561	2561000000	CT-561 T	3560000000	CT-562	3561000000	CT-562 T
120	Х	80	Х	55	2580000000	CT-581	2581000000	CT-581 T	3580000000	CT-582	3581000000	CT-582 T
120	Х	80	Х	85	2600000000	CT-601	2601000000	CT-601 T	3600000000	CT-602	3601000000	CT-602 T
160	Х	80	Х	55	262000000	CT-621	2621000000	CT-621 T	3620000000	CT-622	3621000000	CT-622 T
160	Х	80	Х	85	2640000000	CT-641	2641000000	CT-641 T	3640000000	CT-642	3641000000	CT-642 T
122	Х	120	Х	55	2660000000	CT-661	2661000000	CT-661 T	3660000000	CT-662	3661000000	CT-662 T
122	Х	120	Х	85	2680000000	CT-681	2681000000	CT-681 T	3680000000	CT-682	3681000000	CT-682 T
160	Х	120	Х	90	2720000000	CT-721	2721000000	CT-721 T	3720000000	CT-722	3721000000	CT-722 T
200	Х	120	Х	75	2760000000	CT-761	2761000000	CT-761 T	3760000000	CT-762	3761000000	CT-762 T
200	Х	120	Х	90	2780000000	CT-781	2781000000	CT-781 T	3780000000	CT-782	3781000000	CT-782 T
240	Х	120	Х	100	2800000000	CT-801	2801000000	CT-801 T	3800000000	CT-802	3801000000	CT-802 T
200	Х	150	Х	75	282000000	CT-821	2821000000	CT-821 T	3820000000	CT-822	3821000000	CT-822 T
240	Х	160	Х	90	2840000000	CT-841	2841000000	CT-841 T	3840000000	CT-842	3841000000	CT-842 T
240	Х	160	х	120	2860000000	CT-861	2861000000	CT-861 T	3860000000	CT-862	3861000000	CT-862 T
250	Х	160	Х	90	2900000000	CT-901	2901000000	CT-901 T	390000000	CT-902	3901000000	CT-902 T
250	Х	160	х	120	2910000000	CT-911	2911000000	CT-911 T	3910000000	CT-912	3911000000	CT-912 T
360	Х	200	Х	150	2880000000	CT-881	2881000000	CT-881 T	3880000000	CT-882	3881000000	CT-882 T
300	Х	230	х	86	2870000000	CT-871	2871000000	CT-871 T	3870000000	CT-872	3871000000	CT-872 T
300	Х	230	Х	110	289000000	CT-891	2891000000	CT-891 T	3890000000	CT-892	3891000000	CT-892 T

Assembling of components



This is just a selection of possible assembly components that BERNSTEIN offers. Contact us, we can incorporate components from all leading manufacturers to satisfy your individual demand. You find further information about "System solutions" on page 12.



Mounting plates

Made from laminated paper (Pertinax) (thickness: CT-50 to CT-60: 1.5 mm; CT-62 to CT-78: 2.0 mm; CT-80 to CT-91; 2.5 mm) for versatile mounting of built-in components.



Mounting rails

conforming to standards TS15 or TS32 and TS 35 made from steel; surface treated for accepting terminal blocks.



Terminal blocks

of all renowned manufacturers are used.



Earthing bars

made from galvanised steel for combining and connecting PE conductors.



External mounting brackets

made from polycarbonate for mounting enclosures without opening the covers. Different bracket arrangement options offset by 90°. Colour RAL 7035.



External articulated hinges

made from polycarbonate for hinged mounting of enclosure cover. Opening range of cover approx. 195°, latching at 170°, articulated hinges are simply pressed into holes (CT-88: secured by screws).



Flexible quick-release fastener/internal articulated hinges

for captive mounting and strain relief for enclosure cover. Cover opening range > 180°. Stainless steel with injection-moulded polyamide ends.



Silicon, EPDM or HF seal

with increased temperature resistance (see indications left side) or to protect sensitive electronic equipment against high-frequency radiation (HF seal). If a HF seal is used, an additional coating of the inside of the enclosure is required.



Brass press-in bushes

with metric fastening screws M3 (M4 on CT-88), for mounting built-in components with metric screws in the mounting bushes in the enclosure body.



Cable glands

Euro-2000 (Euro-Top) screwed cable glands, plastic (polyamide 6, RAL 7035), including integrated strain relief. Sealing element NEOPRENE. Temperature range: –30°C bis +80°C (see also page 71). Other cable glands on demand.




52 x 50 x 35 mm

CT-501 Polycarbonate enclosures CT-502 ABS enclosures

BODY 52 47/46.5* 30/29.5* BODY 52 47/46.5* 30/29.5* BEALTH COVER BODY 52 47/46.5* 30/29.5* BEALTH COVER BEALT

65 x 50 x 35 mm

CT-521 Polycarbonate enclosures CT-522 ABS enclosures



^{*} Smaller dimension at mounting plate support

Туре										CT-501 PC	CT-502 ABS
Weight (g)										40 (PC)	38 (ABS)
External di	mensio	on (m	m)							52 x 50 x 3	5
Ordering o	lata Er	nclosu	ıre (p	ainte	d) wit	h sea	l (PUF	R)		Part numb	er
PC, with qu	iick-rel	ease	faster	ner						25000000	00
PC, with sc	rew fa	stene	r							25000010	00
PC, with tra	nspar	ent co	over (l	PC) ar	nd qu	ick-re	lease	faster	er	25010000	00
ABS, with o	uick-r	elease	e faste	ener						35000000	00
ABS, with s	crew f	asten	er							35000010	00
ABS, with t	ranspa	arent (cover	(PC)	and q	uick-	releas	e faste	ener	35010000	00
Accessorie	s (indi	vidua	l part	or in	stalla	tion k	it)				
Mounting p	olate									95120090	00
Mounting r	ail TS	15								-	
Mounting r	ail TS 3	32								-	
Mounting r	ail TS 3	35								-	
Earthing ra	il (secu	ired o	n cer	tral b	osses	s C/D)				-	
External me	ountin	g bra	ckets							_	
External art	iculate	ed hir	iges*	+						-	
Internal art	iculate	d hin	ges, f	lexibl	e,						
for enclosu	re with	n quic	k-rele	ase fa	asten	er				-	
Silicone sea	al for e	xtend	led te	mper	ature	rang	e (by	the m	etre)	_	
Mounting I	oushes	with	4 scr	ews N	13 x 8					-	
Maximum	possil	ole nu	ımbe	r of t	hrea	ds					
ISO M	12	16	20	25	32	40	50	63			
Side A/B	1	0	0	0	0	0	0	0			
Side C/D	1	0	0	0	0	0	0	0			
** Enclosur	o prop	aratio	n rec	uired							

^{*} Smaller dimension at mounting plate support

Туре									(CT-521 PC	CT-522 ABS
Weight (g)									5	50 (PC)	47 (ABS)
External din	nensio	n (m	m)						6	55 x 50 x 3	5
Ordering d	ata En	closu	re (pa	ainted	d) wit	h seal	(PUR)	F	Part num	ber
PC, with qu	ick-rel	25200000	000								
PC, with scr	ew fas	2	25200010	000							
PC, with tra	nspare	r 2	25210000	000							
ABS, with q	uick-re	elease	faste	ener					3	35200000	000
ABS, with s	crew fa	sten	er						3	35200010	000
ABS, with to	ranspa	rent (over	(PC) a	and q	uick-r	eleas	e fasten	er 3	35210000	000
Accessorie	s (indi	vidua	l part	or in	stalla	tion k	it)				
Mounting p	late								9	95120100	000
Mounting ra	ail TS 1	5							9	98200010	000
Mounting ra	ail TS 3	2							-	-	
Mounting ra	ail TS 3	5							-	-	
Earthing rai	l (secu	red o	n cer	itral b	osses	C/D)		-			
External mo	ounting	g bra	ckets						-	-	
External art	iculate	d hir	ges*	+					-	-	
Internal arti	culate	d hin	ges, f	lexibl	e,						
for enclosur	e with	quic	k-rele	ase fa	asten	er			-	-	
Silicone sea	I for ex	ctend	ed te	mper	ature	range	e (by t	the met	re) -	-	
Mounting b	oushes	with	4 scr	ews N	13 x 8				9	98000250	000
Maximum	possil	ole nu	ımbe	r of t	hrea	ds					
ISO M	12	16	20	25	32	40	50	63			
Side A/B	2	0	0	0	0	0	0	0			
Side C/D	0	0	0	0	0	0	0	0			
** Enclosure	e prep	aratio	n rec	uired	I						





82 x 80 x 55 mm

CT-541 Polycarbonate enclosures CT-542 ABS enclosures

82 x 80 x 85 mm

CT-561 Polycarbonate enclosures CT-562 ABS enclosures





^{*} Smaller dimension at mounting plate support

Weight (g) 140 (PC) 116 (ABS) External dimension (mm) 82 x 80 x 55 Ordering data Enclosure (painted) with seal (PUR) Part number PC, with quick-release fastener 2540000000 PC, with screw fastener 2540000000 PC, with transparent cover (PC) and quick-release fastener 3540000000 ABS, with quick-release fastener 3540000000 ABS, with screw fastener 3540000000 ABS, with transparent cover (PC) and quick-release fastener 3540000000 ABS, with transparent cover (PC) and quick-release fastener 3540000000 ACCESSORIES (individual part or installation kit) Mounting plate 9512011000 Mounting rail TS 15 9820004000 Mounting rail TS 35 9822000000 External mounting brackets 9802002000 External mounting brackets 9802002000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0 0 0 Side C/D 2 1 0 0 0 0 0 0			
External dimension (mm) 82 x 80 x 55 Ordering data Enclosure (painted) with seal (PUR) PC, with quick-release fastener PC, with quick-release fastener PC, with screw fastener PC, with transparent cover (PC) and quick-release fastener 254000000 ABS, with quick-release fastener 354000000 ABS, with screw fastener 3540001000 ABS, with transparent cover (PC) and quick-release fastener 3541000000 ABS, with transparent cover (PC) and quick-release fastener 3541000000 ACCESSORIES (individual part or installation kit) Mounting plate 9512011000 Mounting rail TS 15 9820004000 Mounting rail TS 32 - Mounting rail (secured on central bosses C/D) External mounting brackets 9802002000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0 0	••	CT-541 PC	CT-542 ABS
Ordering data Enclosure (painted) with seal (PUR) PC, with quick-release fastener PC, with quick-release fastener PC, with screw fastener PC, with screw fastener PC, with screw fastener PC, with screw fastener PC, with transparent cover (PC) and quick-release fastener PC, with quick-release fastener PC, with transparent cover (PC) and quick-release fastener PC, with screw fastener PC, with screw fastener PC, with screws fastener PC	Weight (g)	140 (PC)	116 (ABS)
PC, with quick-release fastener 254000000 PC, with screw fastener 254000000 PC, with transparent cover (PC) and quick-release fastener 354000000 ABS, with quick-release fastener 354000000 ABS, with screw fastener 3540001000 ABS, with transparent cover (PC) and quick-release fastener 3541000000 ABS, with transparent cover (PC) and quick-release fastener 3541000000 ACCESSORIES (individual part or installation kit) Mounting plate 9512011000 Mounting rail TS 15 9820004000 Mounting rail TS 32	External dimension (mm)	82 x 80 x 55	5
PC, with screw fastener PC, with transparent cover (PC) and quick-release fastener PC, with transparent cover (PC) and quick-release fastener ABS, with quick-release fastener ABS, with screw fastener ABS, with transparent cover (PC) and quick-release fastener ABS, with transparent cover (PC) and quick-release fastener ACCESSORIES (individual part or installation kit) MOUNTING Plate MOUNTING Plate MOUNTING PAIL TS 15 MOUNTING PAIL TS 32 MOUNTING PAIL TS 35 PARE 2000000 External mounting brackets PARE 20000000 External articulated hinges** PARE 20000000 External articulated hinges, flexible, for enclosure with quick-release fastener MOUNTING PAIL TS AS PARE 20000000 External articulated hinges, flexible, for enclosure with quick-release fastener Silicone seal for extended temperature range (by the metre) on request MOUNTING bushes with 4 screws M3 x 8 PARE 20000000 MAXIMUM POSSIBLE NUMBER OF THEADS ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0 0	Ordering data Enclosure (painted) with seal (PUR)	Part numb	er
PC, with transparent cover (PC) and quick-release fastener ABS, with quick-release fastener ABS, with screw fastener ABS, with screw fastener ABS, with transparent cover (PC) and quick-release fastener ABS, with transparent cover (PC) and quick-release fastener ACCESSORIES (individual part or installation kit) Mounting plate Mounting plate Mounting rail TS 15 Mounting rail TS 32 Mounting rail (secured on central bosses C/D) External mounting brackets P802002000 External articulated hinges** P802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener Mounting bushes with 4 screws M3 x 8 P800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 0 0 0 0 0 1541000000 3541000000 3541000000 3541000000 3541000000 3541000000 3541000000 3541000000 3541000000 3541000000 3541000000 3620000000 3620000000 3620000000 3620000000000	PC, with quick-release fastener	25400000	00
ABS, with quick-release fastener ABS, with screw fastener ABS, with screw fastener ABS, with transparent cover (PC) and quick-release fastener ACCESSORIES (individual part or installation kit) Mounting plate Mounting rail TS 15 Mounting rail TS 32 Mounting rail (secured on central bosses C/D) External mounting brackets P802002000 External articulated hinges** P802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener Mounting bushes with 4 screws M3 x 8 P800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 0 354000000 3541000000 3541000000 3541000000 3541000000 3541000000 3640000000 364000000000000 3640000000000	PC, with screw fastener	254000100	00
ABS, with screw fastener ABS, with transparent cover (PC) and quick-release fastener ACCESSORIES (individual part or installation kit) Mounting plate Mounting rail TS 15 Mounting rail TS 32 Mounting rail (secured on central bosses C/D) External mounting brackets External articulated hinges** 9802025000 External articulated hinges, flexible, for enclosure with quick-release fastener Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 0 0 0 0 0 0 0 0 0 0 0 0	PC, with transparent cover (PC) and quick-release fastener	25410000	00
ARS, with transparent cover (PC) and quick-release fastener Accessories (individual part or installation kit) Mounting plate Mounting rail TS 15 Mounting rail TS 32 Mounting rail (secured on central bosses C/D) External mounting brackets External articulated hinges** 9802025000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 0 0 0 0 0 0 0 10 10 10 10	ABS, with quick-release fastener	35400000	00
Accessories (individual part or installation kit) Mounting plate 9512011000 Mounting rail TS 15 9820004000 Mounting rail TS 32 - Mounting rail (secured on central bosses C/D) - External mounting brackets 980202000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0 0	ABS, with screw fastener	354000100	00
Mounting plate 9512011000 Mounting rail TS 15 9820004000 Mounting rail TS 32 Mounting rail (secured on central bosses C/D) External mounting brackets 980202000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0 0	ABS, with transparent cover (PC) and quick-release fastener	35410000	00
Mounting plate 9512011000 Mounting rail TS 15 9820004000 Mounting rail TS 32 Mounting rail (secured on central bosses C/D) External mounting brackets 980202000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0 0			
Mounting plate 9512011000 Mounting rail TS 15 9820004000 Mounting rail TS 32 Mounting rail (secured on central bosses C/D) External mounting brackets 980202000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0 0			
Mounting rail TS 15 9820004000 Mounting rail TS 32 - 9822000000 Earthing rail (secured on central bosses C/D) - External mounting brackets 980202000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0 0	Accessories (individual part or installation kit)		
Mounting rail TS 32 - Mounting rail (secured on central bosses C/D) - External mounting brackets 980202000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0 0	Mounting plate	95120110	00
Mounting rail TS 35 Earthing rail (secured on central bosses C/D) External mounting brackets External articulated hinges** 9802025000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0 0	Mounting rail TS 15	98200040	00
Earthing rail (secured on central bosses C/D) – External mounting brackets 9802025000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0 0	Mounting rail TS 32	-	
External mounting brackets 980202000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0 0	Mounting rail TS 35	98220000	00
## State A	Earthing rail (secured on central bosses C/D)	-	
Internal articulated hinges, flexible, For enclosure with quick-release fastener 9801076000	External mounting brackets	98020020	00
for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0	External articulated hinges**	98020250	00
Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0	Internal articulated hinges, flexible,		
Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0	for enclosure with quick-release fastener	98010760	00
Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0	Silicone seal for extended temperature range (by the metre)	on request	
ISO M 12 16 20 25 32 40 50 63 Side A/B 5 2 2 0 0 0 0 0	Mounting bushes with 4 screws M3 x 8	980002500	00
Side A/B 5 2 2 0 0 0 0 0	Maximum possible number of threads		
	ISO M 12 16 20 25 32 40 50 63		
Side C/D 2 1 0 0 0 0 0 0	Side A/B 5 2 2 0 0 0 0 0		
	Side C/D 2 1 0 0 0 0 0 0		
** Enclosure preparation required	** Enclosure preparation required		

^{*} Smaller dimension at mounting plate support


Гуре	CT-561 PC CT-562 ABS
Weight (g)	175 (PC) 150 (ABS)
External dimension (mm)	82 x 80 x 85
Ordering data Enclosure (painted) with seal (PUR)	Part number
PC, with quick-release fastener	2560000000
PC, with screw fastener	2560001000
PC, with transparent cover (PC) and quick-release fastener	2561000000
ABS, with quick-release fastener	3560000000
ABS, with screw fastener	3560001000
ABS, with transparent cover (PC) and quick-release fastener	3561000000
Accessories (individual part or installation kit)	
Mounting plate	9512011000
Mounting rail TS 15	9820004000
Mounting rail TS 32	-
Mounting rail TS 35	9822000000
Earthing rail (secured on central bosses C/D)	-
External mounting brackets	9802002000
External articulated hinges**	9802025000
nternal articulated hinges, flexible,	
for enclosure with quick-release fastener	9801076000
Silicone seal for extended temperature range (by the metre)	on request
Mounting bushes with 4 screws M3 x 8	9800025000
Maximum possible number of threads	
SO M 12 16 20 25 32 40 50 63	
Side A/B 10 5 3 2 1 1 1 0	
Side C/D 5 2 1 1 1 0 0 0	
** Enclosure preparation required	

120 x 80 x 55 mm

CT-581 Polycarbonate enclosures CT-582 ABS enclosures

120 x 80 x 85 mm

CT-601 Polycarbonate enclosures CT-602 ABS enclosures



^{*} Smaller dimension at mounting plate support

Туре									(CT-581 PC	CT-582 ABS
Weight (g)										180 (PC)	135 (ABS)
External di	mensic	n (m	m)							120 x 80 x	55
Ordering o	data Er	nclosu	ure (p	ainte	d) wit	h sea	l (PUF	()	Ī	Part numl	per
PC, with qu	uick-rel	ease	faster	ner					:	25800000	00
PC, with so	rew fas	stene	r						:	25800010	000
PC, with tra	anspar	ent co	over (l	PC) ar	nd qu	ick-re	lease	fastene	er 2	25810000	000
ABS, with	quick-r	eleas	e faste	ener						35800000	000
ABS, with	screw f	asten	er						3	35800010	000
ABS, with t	transpa	rent	cover	(PC)	and q	uick-	releas	e faster	ner :	35810000	000
Accessorie	s (indi	vidua	l part	or in	stalla	tion k	it)				
Mounting	plate								9	95120120	000
Mounting	rail TS 1	15							9	98200090	000
Mounting	rail TS 3	32								-	
Mounting	rail TS 3	35							9	98220020	000
Earthing ra	il (secu	ired c	n cer	itral b	osses	s C/D)			9	98100010	000
External m	ountin	g bra	ckets						9	98020020	000
External ar	ticulate	ed hir	nges*	*					9	98020250	000
Internal art	ticulate	d hin	iges, f	lexibl	e,						
for enclosu	ıre with	quic	k-rele	ease fa	asten	er			9	98010760	000
Silicone sea	al for e	xtend	led te	mper	ature	rang	e (by	the met	tre) a	auf Anfra	ge
Mounting	bushes	with	4 scre	ews N	13 x 8				9	98000400	000
Maximum	possil	ole ni	umbe	r of t	hrea	ds					
ISO M	12	16	20	25	32	40	50	63			
Side A/B	9	4	3	2	0	0	0	0			
Side C/D	2	1	1	0	0	0	0	0			
** Enclosur	re prep	aratio	on rec	uired							

^{*} Smaller dimension at mounting plate support

Type									CT-601 P	C CT-602 ABS			
Weight (g)									225 (PC)	192 (ABS)			
External dime	ensior	120 x 80 x	85										
Ordering dat	Part num	Part number											
PC, with quic	000												
PC, with screv	PC, with screw fastener PC, with transparent cover (PC) and guick-release fastener 260												
PC, with trans	parei	nt co	ver (P	C) an	d qui	ck-rel	ease	fastener	2601000	000			
ABS, with qui	ck-rel	lease	faste	ner					3600000	000			
ABS, with scr	ew fa	stene	r						3600001	000			
ABS, with tra	r 3601000	000											
Accessories (indivi	idual	part o	or ins	tallati	ion kit	t)						
Mounting plate 9512012000													
Mounting rail TS 15 9820009000													
Mounting rail	TS 32	2							-				
Mounting rail	TS 35	5							9822002	000			
Earthing rail (secur	ed or	n cent	ral bo	osses	C/D)			9810001	000			
External mou	nting	brac	kets						9802002	000			
External artic	ulated	d hing	ges**						9802025	000			
Internal articu	ılated	l hing	jes, fle	exible	·,								
for enclosure	with	quick	-relea	se fa	stene	r			9801076	000			
Silicone seal f	or ext	tende	ed ten	npera	ture	range	(by t	he metre	on reque	st			
Mounting bu	shes v	with 4	1 scre	ws M	3 x 8				9800025	000			
Maximum possible number of threads													
ISO M	12	16	20	25	32	40	50	63					
Side A/B	15	6	6	3	2	1	1	0					
Side C/D	5	2	1	1	1	0	0	0					
** Enclosure	orepa	ratio	ı requ	iired									





160 x 80 x 55 mm

CT-621 Polycarbonate enclosures CT-622 ABS enclosures

160 x 80 x 85 mm

CT-641 Polycarbonate enclosures CT-642 ABS enclosures





^{*} Smaller dimension at mounting plate support

Туре	CT-621 PC	CT-622 ABS
Weight (g)	225 (PC)	199 (ABS)
External dimension (mm)	160 x 80 x 5	55
Ordering data Enclosure (painted) with seal (PUR)	Part numb	er
PC, with quick-release fastener	26200000	00
PC, with screw fastener	26200010	00
PC, with transparent cover (PC) and quick-release fastener	26210000	00
ABS, with quick-release fastener	36200000	00
ABS, with screw fastener	36200010	00
ABS , with transparent cover (PC) and quick-release fastener	36210000	00
Accessories (individual part or installation kit)		
Mounting plate	95120130	00
Mounting rail TS 15	98200130	00
Mounting rail TS 32	-	
Mounting rail TS 35	98220280	00
Earthing rail (secured on central bosses C/D)	98100050	00
External mounting brackets	98020020	00
External articulated hinges**	98020250	00
Internal articulated hinges, flexible,		
for enclosure with quick-release fastener	98010760	00
Silicone seal for extended temperature range (by the metre)	on request	:
Mounting bushes with 4 screws M3 x 8	98000400	00
Maximum possible number of threads		
ISO M 12 16 20 25 32 40 50 63		
Side A/B 11 5 4 3 0 0 0 0		
Side C/D 2 1 1 0 0 0 0 0		

^{*} Smaller dimension at mounting plate support

Weight (g) External dimension (mm) Condering data Enclosure (painted) with seal (PUR) Part number 2640000000 PC, with quick-release fastener 2640000000 PC, with screw fastener 2640000000 PC, with transparent cover (PC) and quick-release fastener 2641000000 ABS, with quick-release fastener 3640000000 ABS, with screw fastener 3640000000 ABS, with transparent cover (PC) and quick-release fastener 3641000000 ABS, with transparent cover (PC) and quick-release fastener 3641000000 ACCESSORIES (individual part or installation kit) Mounting plate Mounting plate Mounting rail TS 15 9820013000 Mounting rail TS 35 9820228000 External mounting brackets External articulated hinges** 9802025000 Texternal articulated hinges, flexible, for enclosure with quick-release fastener Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads SO M 12 16 20 25 32 40 50 63 666 663 666 666 666 666											
Conternal dimension (mm) Contering data Enclosure (painted) with seal (PUR) Part number PC, with quick-release fastener Contering data Enclosure (painted) with seal (PUR) Part number 2640000000 PC, with quick-release fastener 2640001000 PC, with transparent cover (PC) and quick-release fastener 2641000000 ABS, with quick-release fastener 3640001000 ABS, with screw fastener 3640001000 ABS, with transparent cover (PC) and quick-release fastener 3641000000 ACCESSORIES (individual part or installation kit) Mounting plate 9512013000 Mounting rail TS 15 9820013000 Mounting rail TS 35 9822028000 External mounting brackets Scarthing rail (secured on central bosses C/D) External articulated hinges** 9802025000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 External articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 External articulated hinges, flexible, for enclosure hinges, flexible, for enclosure	Туре									CT-641 PC CT-642 A	BS
Ordering data Enclosure (painted) with seal (PUR) Part number 26, with quick-release fastener 264000000 PC, with screw fastener 264000000 PC, with screw fastener 264000000 PC, with transparent cover (PC) and quick-release fastener 364000000 ABS, with quick-release fastener 3640001000 ABS, with screw fastener 3640001000 ABS, with transparent cover (PC) and quick-release fastener 3641000000 ACCESSORIES (individual part or installation kit) Mounting plate Mounting plate Mounting rail TS 15 Mounting rail TS 35 PS20013000 External mounting brackets PS0000000 External articulated hinges** 9802025000 External articulated hinges, flexible, for enclosure with quick-release fastener Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 Maximum possible number of threads SO M 12 16 20 25 32 40 50 63 Side A/B 22 10 8 5 3 2 2 0 Side C/D 5 2 1 1 1 0 0 0 0	Weight (g)									240 (PC) 225 (ABS)
PC, with quick-release fastener PC, with screw fastener PC, with screw fastener PC, with transparent cover (PC) and quick-release fastener PC, with quick-release fastener PC, with transparent cover (PC) and quick-release fastener PC, with quick-release fastener PS P	External dim	ensio	n (mn	n)						160 x 80 x 85	
Accessories (individual part or installation kit) Mounting plate Mounting rail TS 35 Mounting rail TS 35 Activiting rail (secured on central bosses C/D) External mounting brackets External articulated hinges** To renclosure with quick-release fastener Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 Maximum possible number of threads SO M 12 16 20 25 32 40 50 63 Side A/B 22 10 8 5 3 2 2 0 Side C/D 5 2 1 1 1 1 0 0 0 0	Ordering da	ita En	closu	re (pa	inted	l) with	n seal	(PUR)	Part number	
Accessories (individual part or installation kit) Accessories (individual part or installation kit) Accessories (individual part or installation kit) Mounting plate Mounting rail TS 15 Mounting rail TS 35 Accessories (individual base of the part of the	PC, with quid	ck-rele	ease f	asten	er					264000000	
ABS, with quick-release fastener 364000000 ABS, with screw fastener 3640001000 ABS, with transparent cover (PC) and quick-release fastener 3641000000 ACCESSORIES (individual part or installation kit) Mounting plate 9512013000 Mounting rail TS 15 9820013000 Mounting rail TS 32	PC, with scre	w fas	tener							2640001000	
ABS, with screw fastener 3640001000 ABS, with transparent cover (PC) and quick-release fastener 3641000000 Accessories (individual part or installation kit) Mounting plate 9512013000 Mounting rail TS 15 9820013000 Mounting rail TS 35 9822028000 Earthing rail (secured on central bosses C/D) 9810005000 External mounting brackets 9802002000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) auf Anfrage Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads SO M 12 16 20 25 32 40 50 63 Side A/B 22 10 8 5 3 2 2 0 Side C/D 5 2 1 1 1 1 0 0 0 0	PC, with tran	spare	nt co	ver (P	C) an	d qui	ck-rel	ease	fastener	2641000000	
Accessories (individual part or installation kit) Mounting plate Mounting rail TS 15 Mounting rail TS 35 Mounting rail (secured on central bosses C/D) External mounting brackets External articulated hinges** More renclosure with quick-release fastener Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 Maximum possible number of threads SO M 12 16 20 25 32 40 50 63 Side A/B 22 10 8 5 3 2 2 0 Side C/D 5 2 1 1 1 1 0 0 0 0	ABS, with qu	uick-re	lease	faste	ner					364000000	
Accessories (individual part or installation kit) Mounting plate 9512013000 Mounting rail TS 15 9820013000 Mounting rail TS 32 - Mounting rail (secured on central bosses C/D) 9810005000 External mounting brackets 980202000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) auf Anfrage Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads SO M 12 16 20 25 32 40 50 63 Side A/B 22 10 8 5 3 2 2 0 Side C/D 5 2 1 1 1 0 0 0 0	ABS, with sc	rew fa	stene	er						3640001000	
Mounting plate	ABS, with tra	anspa	rent c	over	(PC) a	ınd qı	uick-re	eleas	e fastene	er 3641000000	
Mounting plate											
Mounting plate											
Mounting rail TS 15 9820013000 Mounting rail TS 32 - 9822028000 Earthing rail (secured on central bosses C/D) 9810005000 External mounting brackets 980202000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) auf Anfrage Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads SO M 12 16 20 25 32 40 50 63 Side A/B 22 10 8 5 3 2 2 0 Side C/D 5 2 1 1 1 0 0 0 0	Accessories	(indiv	/idual	part	or ins	tallat	ion ki	t)			
Mounting rail TS 32	Mounting pl	ate								9512013000	
Mounting rail TS 35	Mounting ra	il TS 1	5							9820013000	
## Strick of Company C	Mounting ra	il TS 3	2							-	
## Steep No. 1	Mounting ra	il TS 3	5							9822028000	
## Steen and articulated hinges ** * * * * * * * * * * * * * * * * *	Earthing rail	(secu	red o	n cen	tral b	osses	C/D)			9810005000	
nternal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) auf Anfrage 9800025000 Maximum possible number of threads SO M 12 16 20 25 32 40 50 63 Side A/B 22 10 8 5 3 2 2 0 Side C/D 5 2 1 1 1 0 0 0 0	External mou	unting	g brac	kets						9802002000	
For enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads SO M 12 16 20 25 32 40 50 63 Side A/B 22 10 8 5 3 2 2 0 Side C/D 5 2 1 1 1 0 0 0 0	External artic	culate	d hin	ges**						9802025000	
## Silicone seal for extended temperature range (by the metre) ## Support	Internal artic	ulate	d hing	ges, fl	exible	2,					
Mounting bushes with 4 screws M3 x 8 9800025000 Maximum possible number of threads SO M 12 16 20 25 32 40 50 63 Side A/B 22 10 8 5 3 2 2 0 Side C/D 5 2 1 1 1 1 0 0 0 0	for enclosure	e with	quick	k-rele	ase fa	stene	er			9801076000	
Maximum possible number of threads SO M 12 16 20 25 32 40 50 63 Side A/B 22 10 8 5 3 2 2 0 Side C/D 5 2 1 1 1 0 0 0	Silicone seal	for ex	tende	ed ter	npera	ature	range	(by t	he metr	e) auf Anfrage	
SO M 12 16 20 25 32 40 50 63 Side A/B 22 10 8 5 3 2 2 0 Side C/D 5 2 1 1 1 0 0 0	Mounting bu	ushes	with 4	4 scre	ws M	3 x 8				9800025000	
Side A/B 22 10 8 5 3 2 2 0 Side C/D 5 2 1 1 1 0 0 0	Maximum p	ossib	le nu	mbe	of th	read	ls				
Side C/D 5 2 1 1 1 0 0 0	ISO M	12	16	20	25	32	40	50	63		
	Side A/B	22	10	8	5	3	2	2	0		
* Enclosure preparation required	Side C/D	5	2	1	1	1	0	0	0		
	** Enclosure	prepa	aratio	n req	uired						


122 x 120 x 55 mm

CT-661 Polycarbonate enclosures CT-662 ABS enclosures

BODY 122 116/115* 98.5/97.5* A 83.5 BODY 120 110 BODY 121 100 B 110

122 x 120 x 85 mm

CT-681 Polycarbonate enclosures CT-682 ABS enclosures



^{*} Smaller dimension at mounting plate support

Туре										CT-661 PC	CT-662 ABS
Weight (g)										240 (PC)	218 (ABS)
External di	mensic	n (m	m)							122 x 120 x	55
Ordering of	data Er	ıclosı	ıre (p	ainte	d) wit	h seal	(PUF	R)		Part numb	er
PC, with qu	uick-rel	ease	faster	ner						26600000	00
PC, with sc	rew fas	tene	r							26600010	00
PC, with tra	anspare	ent co	over (l	PC) aı	nd qu	ick-re	lease	faster	er	26610000	00
ABS, with	quick-re	eleas	e faste	ener						36600000	00
ABS, with s	screw f	asten	er							36600010	00
ABS, with t	transpa	rent	cover	(PC)	and q	uick-ı	releas	e faste	ener	36610000	00
Accessorie	s (indi	vidua	l part	or in	stalla	tion k	it)				
Mounting	plate									95120140	00
Mounting I	rail TS 1	5								98200080	00
Mounting I	rail TS 3	32								-	
Mounting I	rail TS 3	35								98220020	00
Earthing ra	il (secu	ired c	n cer	itral b	osses	C/D)				98100030	00
External m	ountin	g bra	ckets							98020020	00
External ar	ticulate	ed hir	nges*	K -						98020250	00
Internal art	iculate	d hin	ges, f	lexibl	e,						
for enclosu	ire with	quic	k-rele	ease f	asten	er				98010760	00
Silicone sea	al for ex	ktend	led te	mper	ature	rang	e (by	the m	etre)	on reques	t
Mounting I	bushes	with	4 scr	ews N	13 x 8					98000250	00
Maximum	possik	ole ni	umbe	r of t	hrea	ds					
ISO M	12	16	20	25	32	40	50	63			
Side A/B	9	4	3	2	0	0	0	0			
Side C/D	4	3	2	0	0	0	0	0			
** Enclosur	e prep	aratio	n rec	uirec							

^{*} Smaller dimension at mounting plate support

Туре	CT-681 PC CT-682 ABS											
Weight (g)	295 (PC) 269 (ABS)											
External dimension (mm) 122 x 120 x 85 Ordering data Enclosure (painted) with seal (PUR) Part number												
Ordering data Enclosure (painted) with seal (PUR) Part number												
PC, with quick-release fastener 268000000												
PC, with screw fastener 2680001000												
PC, with transparent cover (PC) and quick-release fastener	r 2681000000											
ABS, with quick-release fastener 3680000000												
ABS, with screw fastener 3680001000												
ABS, with transparent cover (PC) and quick-release fasten	er 3681000000											
Accessories (individual part or installation kit)												
Mounting plate 9512014000												
Mounting rail TS 15 –												
Mounting rail TS 32	9821001000											
Mounting rail TS 35	9822002000											
Earthing rail (secured on central bosses C/D)	9810003000											
External mounting brackets	9802002000											
External articulated hinges**	9802025000											
Internal articulated hinges, flexible,												
for enclosure with quick-release fastener	9801076000											
Silicone seal for extended temperature range (by the met	re) on request											
Mounting bushes with 4 screws M3 x 8 9800025000												
Maximum possible number of threads												
ISO M 12 16 20 25 32 40 50 63												
Side A/B 15 6 6 3 20 1 1 0												
Side C/D 10 3 3 2 1 0 0 0												
** Enclosure preparation required												



160 x 120 x 90 mm


CT-721 Polycarbonate enclosures CT-722 ABS enclosures

(COVER) Ē 84.5 10.5 4.5 x 5.5 BODY 160 154/153* 136.5/135.5 * A • **6** 76.5/75.5* 120 114/113* 120 © 136 • [

200 x 120 x 75 mm

CT-761 Polycarbonate enclosures CT-762 ABS enclosures

CAD files available at www.bernstein.eu



B 148.2

Туре	CT-721 PC	CT-722 ABS
Weight (g)	360 (PC)	310 (ABS)
External dimension (mm)	160 x 120 x	90
Ordering data Enclosure (painted) with seal (PUR)	Part numb	er
PC, with quick-release fastener	27200000	00
PC, with screw fastener	27200010	00
PC, with transparent cover (PC) and quick-release fastener	27210000	00
ABS, with quick-release fastener	37200000	00
ABS, with screw fastener	37200010	00
ABS, with transparent cover (PC) and quick-release fastener	37210000	00
Accessories (individual part or installation kit)		
Mounting plate	95120360	00
Mounting rail TS 15	-	
Mounting rail TS 32	98210250	00
Mounting rail TS 35	98220280	00
Earthing rail (secured on central bosses C/D)	98100400	00
External mounting brackets	98020020	00
External articulated hinges**	98020250	00
Internal articulated hinges, flexible,		
for enclosure with quick-release fastener	98010790	00
Silicone seal for extended temperature range (by the metre)	on request	t
Mounting bushes with 4 screws M3 x 8	98000250	00
Maximum possible number of threads		
ISO M 12 16 20 25 32 40 50 63		
Side A/B 18 10 7 3 3 0 0 0		
Side C/D 9 5 2 2 1 0 0 0		
Side C/D 9 3 2 2 1 0 0 0		

^{*} Smaller dimension at mounting plate support

Туре									CT-761 PC	CT-762 ABS	
Weight (g)									400 (PC)	373 (ABS)	
External dime	ensio	n (mn	า)						200 x 120 x	75	
Ordering dat	Part numb	er									
PC, with quic	27600000	2760000000									
PC, with screv	w fast	tener							27600010	00	
PC, with trans	spare	nt co	ver (P	C) an	d qui	ck-rel	ease	fastener	27610000	00	
ABS, with qui	ick-re	lease	faste	ner					37600000	00	
ABS, with scr	ew fa	stene	r						37600010	00	
ABS, with tra	nspar	ent c	over	(PC) a	nd qı	uick-re	elease	e fastener	37610000	00	
Accessories (individual part or installation kit)											
Mounting pla	ite								95120150	00	
Mounting rail	TS 1	5							-		
Mounting rail	TS 32	2							9821004000		
Mounting rail	TS 3	5							98220060	00	
Earthing rail (secur	red or	n cent	tral bo	osses	C/D)			98100060	00	
External mou	nting	brac	kets						98020020	00	
External artic	ulate	d hing	ges**						98020250	00	
Internal articu	ulated	d hing	jes, fl	exible	2,						
for enclosure	with	quick	-rele	ase fa	stene	er			98010760	00	
Silicone seal f	or ex	tende	ed ter	npera	ture	range	(by t	he metre)	on reques	t	
Mounting bu	shes	with 4	1 scre	ws M	3 x 8				98000400	00	
Maximum po	ossib	le nu	mbei	of th	read	ls					
ISO M	12	16	20	25	32	40	50	63			
Side A/B	26	12	8	5	3	0	0	0			
Side C/D	10	5	2	2	1	0	0	0			
** Enclosure	orepa	ratio	n requ	uired							


^{*} Smaller dimension at mounting plate support

200 x 120 x 90 mm

CT-781 Polycarbonate enclosures CT-782 ABS enclosures

240 x 120 x 100 mm

CT-801 Polycarbonate enclosures CT-802ABS enclosures



^{*} Smaller dimension at mounting plate support

Туре	CT-781 PC	CT-782 ABS								
Weight (g)	420 (PC)	365 (ABS)								
External dimension (mm)	200 x 120 x	90								
Ordering data Enclosure (painted) with seal (PUR)	Part numb	er								
PC, with quick-release fastener	27800000	00								
PC, with screw fastener	27800010	00								
PC , with transparent cover (PC) and quick-release fastener	27810000	00								
ABS, with quick-release fastener	37800000	00								
ABS, with screw fastener	37800010	00								
ABS, with transparent cover (PC) and quick-release fastener	37810000	00								
Accessories (individual part or installation kit)										
Mounting plate	95120150	00								
Mounting rail TS 15	-									
Mounting rail TS 32	98210040	00								
Mounting rail TS 35	98220060	00								
Earthing rail (secured on central bosses C/D)	98100060	00								
External mounting brackets	98020020	00								
External articulated hinges**	98020250	00								
Internal articulated hinges, flexible,										
for enclosure with quick-release fastener	98010790	00								
Silicone seal for extended temperature range (by the metre	on reques	t								
Mounting bushes with 4 screws M3 x 8	98000400	00								
Maximum possible number of threads										
ISO M 12 16 20 25 32 40 50 63										
Side A/B 26 12 8 5 3 0 0 0										
Side C/D 10 5 2 2 1 0 0 0										
** Enclosure preparation required										

^{*} Smaller dimension at mounting plate support

Туре										CT-801 PC CT-8	302 ABS	
Weight (g)										540 (PC) 478	(ABS)	
External dim	ensio	n (mr	n)							240 x 120 x 100		
Ordering da	ta En	Part number										
PC, with quic	2800000000											
PC, with scre	2800001000											
PC, with tran	2801000000											
ABS, with qu	ick-re	lease	faste	ner						3800000000		
ABS, with sci	ew fa	stene	er							3800001000		
ABS, with tra	nspa	rent c	over	(PC) a	nd q	uick-r	elease	e fasten	er	3801000000		
Accessories	(indiv	/idual	part	or ins	tallat	ion ki	t)					
Mounting pla	ate									9512016000		
Mounting rai	ITS 1	5								-		
Mounting rai	ITS 3	2								9821006000		
Mounting rai	ITS 3	5								9822008000		
Earthing rail	(secu	red o	n cen	tral b	osses	C/D)				9810009000		
External mou	ınting	g brac	kets							9802002000		
External artic	ulate	d hin	ges**							9802025000		
Internal artic	ulate	d hing	ges, fl	exible	2,							
for enclosure	with	quicl	c-rele	ase fa	stene	er				9801078000		
Silicone seal	for ex	tend	ed ter	npera	ature	range	(by t	he met	re)	on request		
Mounting bu	ishes	with 4	4 scre	ws M	3 x 8					9800025000		
Maximum p	ossib	le nu	mbe	of th	reac	ls						
ISO M	12	16	20	25	32	40	50	63				
Side A/B	34	17	12	6	5	3	3	2				
Side C/D	10	6	3	2	1	1	0	0				
** Enclosure	prepa	ratio	n req	uired								




200 x 150 x 75 mm

CT-821 Polycarbonate enclosures CT-822 ABS enclosures

240 x 160 x 90 mm

CT-841 Polycarbonate enclosures CT-842 ABS enclosures



^{*} Smaller dimension at mounting plate support

Туре	CT-821 PC	CT-822 ABS
Weight (g)	475 (PC)	425 (ABS)
External dimension (mm)	200 x 150 x	75
Ordering data Enclosure (painted) with seal (PUR)	Part numb	er
PC, with quick-release fastener	28200000	00
PC, with screw fastener	28200010	00
PC, with transparent cover (PC) and quick-release fastener	28210000	00
ABS, with quick-release fastener	38200000	00
ABS, with screw fastener	38200010	00
ABS, with transparent cover (PC) and quick-release fastener	38210000	00
Accessories (individual part or installation kit)		
Mounting plate	95120170	00
Mounting rail TS 15	-	
Mounting rail TS 32	98210170	00
Mounting rail TS 35	98220200	00
Earthing rail (secured on central bosses C/D)	98100060	00
External mounting brackets	98020020	00
External articulated hinges**	98020250	00
Internal articulated hinges, flexible,		
for enclosure with quick-release fastener	98010760	00
Silicone seal for extended temperature range (by the metre)	on request	t
Mounting bushes with 4 screws M3 x 8	98000250	00
Maximum possible number of threads		
ISO M 12 16 20 25 32 40 50 63		
Side A/B 22 12 9 5 3 0 0 0		
Side C/D 12 6 3 2 2 0 0 0		

^{*} Smaller dimension at mounting plate support


Туре	CT-841 PC	CT-842 ABS									
Weight (g)	650 (PC)	528 (ABS)									
External dimension (mm)	240 x 160 x	90									
Ordering data Enclosure (painted) with seal (PUR)	Part numb	er									
PC, with quick-release fastener	284000000	00									
PC, with screw fastener	284000100	00									
PC, with transparent cover (PC) and quick-release fastener	284100000	00									
ABS, with quick-release fastener	384000000	00									
ABS, with screw fastener	384000100	00									
ABS, with transparent cover (PC) and quick-release fastener	384100000	00									
Accessories (individual part or installation kit)											
Mounting plate	951201800	00									
Mounting rail TS 15	-										
Mounting rail TS 32	9821006000										
Mounting rail TS 35	982200800	00									
Earthing rail (secured on central bosses C/D)	981000900	00									
External mounting brackets	980200200	00									
External articulated hinges**	980202500	00									
Internal articulated hinges, flexible,											
for enclosure with quick-release fastener	980107600	00									
Silicone seal for extended temperature range (by the metre)	on request	:									
Mounting bushes with 4 screws M3 x 8	980004000	00									
Maximum possible number of threads											
ISO M 12 16 20 25 32 40 50 63											
Side A/B 36 16 12 8 4 2 2 2											
Side C/D 17 8 5 3 2 2 1 0											
** Enclosure preparation required											

240 x 160 x 120 mm

CT-861 Polycarbonate enclosures CT-862 ABS enclosures

250 x 160 x 90 mm

CT-901 Polycarbonate enclosures CT-902 ABS enclosures



^{*} Smaller dimension at mounting plate support

Туре									C.	Г-861 РС	CT-862 ABS			
Weight (g)	Veight (g)									35 (PC)	636 (ABS)			
External di	mensio	on (m	m)						24	240 x 160 x 120				
Ordering data Enclosure (painted) with seal (PUR)										art numb	er			
PC, with qu	uick-re	lease	faster	ner					28	3600000	00			
PC, with sc	rew fa	stene	r						28	3600010	00			
PC, with tra	anspar	ent c	over (PC) aı	nd qu	ick-re	lease	fastene	r 2 8	3610000	00			
ABS, with o	quick-r	eleas	e fast	ener					38	3600000	00			
ABS, with	screw f	asten	er						38	3600010	00			
ABS, with t	ranspa	arent	cover	(PC)	and q	uick-	releas	e faster	ner 38	3610000	00			
Accessorie	s (indi	vidua	ıl part	or in	stalla	tion k	it)							
Mounting	plate								95	5120180	00			
Mounting I	rail TS	15							-					
Mounting I	rail TS	32							98	3210060	00			
Mounting I	rail TS :	35							98	3220080	00			
Earthing ra	il (secu	ured c	n cer	itral k	osses	s C/D)			98	3100090	00			
External m	ountin	g bra	ckets						98	3020020	00			
External ar	ticulat	ed hir	nges*	*					98	3020250	00			
Internal art	iculate	ed hin	iges, f	lexib	le,									
for enclosu	re with	n quic	k-rele	ase f	asten	er			98	3010800	00			
Silicone sea	al for e	xtend	led te	mpei	ature	rang	e (by	the met	re) oı	reques	t			
Mounting I	bushes	with	4 scr	ews N	13 x 8				98	3000400	00			
Maximum	Maximum possible number of threads													
ISO M	12	16	20	25	32	40	50	63						
Side A/B	36	16	12	8	4	2	2	2						
Side C/D	17	8	5	3	2	2	1	0						
** Enclosur	e prep	aratio	on rec	uirec	1									

^{*} Smaller dimension at mounting plate support

Weight (g) External dimension (mm) Cordering data Enclosure (painted) with seal (PUR) Part number PC, with quick-release fastener PC, with quick-release fastener PC, with transparent cover (PC) and quick-release fastener PC, with quick-release fastener PC, with transparent cover (PC) and quick-release fastener PC, with qui											
External dimension (mm) Ordering data Enclosure (painted) with seal (PUR) PC, with quick-release fastener PC, with quick-release fastener PC, with screw fastener PC, with transparent cover (PC) and quick-release fastener PC, with quick-release fastener PC, with quick-release fastener PS12187000 Maccessories (individual part or installation kit) PS12187000 Mounting palte PC, with quick-release fastener PS12187000 PS121870	Туре	CT-901 PC CT-902 ABS									
Ordering data Enclosure (painted) with seal (PUR) PC, with quick-release fastener PC, with quick-release fastener PC, with screw fastener PC, with transparent cover (PC) and quick-release fastener PC, with screw fastener PC, with screws fasten	Weight (g)	680 (PC) 550 (ABS)									
PC, with quick-release fastener 290000000 PC, with screw fastener 2900001000 PC, with transparent cover (PC) and quick-release fastener 390000000 ABS, with quick-release fastener 390000000 ABS, with screw fastener 3900001000 ABS, with transparent cover (PC) and quick-release fastener 390100000 ABS, with transparent cover (PC) and quick-release fastener 3901000000 ACCESSORIES (individual part or installation kit) Mounting plate 9512187000 Mounting rail TS 15	External dimension (mm)	250 x 160 x 90									
PC, with screw fastener PC, with transparent cover (PC) and quick-release fastener PC, with transparent cover (PC) and quick-release fastener PC, with transparent cover (PC) and quick-release fastener PC, with quick-release fastener PC, with transparent cover (PC) and quick-release	Ordering data Enclosure (painted) with seal (PUR)	Part number									
PC, with transparent cover (PC) and quick-release fastener ABS, with quick-release fastener ABS, with screw fastener ABS, with screw fastener ABS, with transparent cover (PC) and quick-release fastener ABS, with transparent cover (PC) and quick-release fastener ACCESSORIES (individual part or installation kit) Mounting plate Mounting rail TS 15 Mounting rail TS 32 Mounting rail (secured on central bosses C/D) External mounting brackets BEATHING RAIL (Secured on central bosses C/D) External articulated hinges** 9802025000 External articulated hinges, flexible, for enclosure with quick-release fastener Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 9800040000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2	PC, with quick-release fastener	2900000000									
ABS, with quick-release fastener 390000000 ABS, with screw fastener 390000000 ABS, with transparent cover (PC) and quick-release fastener 3901000000 ACCESSORIES (individual part or installation kit) Mounting plate 9512187000 Mounting rail TS 15 Mounting rail TS 32 9821006000 Mounting rail (secured on central bosses C/D) 9810009000 External mounting brackets 9802002000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800040000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2 2	PC, with screw fastener	2900001000									
ABS, with screw fastener ABS, with transparent cover (PC) and quick-release fastener ACCESSORIES (individual part or installation kit) Mounting plate Mounting rail TS 15 Mounting rail TS 32 Mounting rail (secured on central bosses C/D) External mounting brackets External articulated hinges** 9802025000 External articulated hinges, flexible, for enclosure with quick-release fastener Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2	PC, with transparent cover (PC) and quick-release fastener	2901000000									
Accessories (individual part or installation kit) Mounting plate Mounting rail TS 15 Mounting rail TS 32 Mounting rail (secured on central bosses C/D) External mounting brackets External articulated hinges** 9802025000 External articulated hinges, flexible, for enclosure with quick-release fastener Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 9800040000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2	ABS, with quick-release fastener	390000000									
Accessories (individual part or installation kit) Mounting plate Mounting rail TS 15 Mounting rail TS 32 Mounting rail (secured on central bosses C/D) External mounting brackets External articulated hinges** 9802025000 External articulated hinges, flexible, for enclosure with quick-release fastener Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 9800040000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2	ABS, with screw fastener	3900001000									
Mounting plate	ABS, with transparent cover (PC) and quick-release fastener	3901000000									
Mounting plate											
Mounting plate											
Mounting rail TS 15 - 9821006000 Mounting rail TS 32 9821006000 Mounting rail (secured on central bosses C/D) 9810009000 External mounting brackets 980202000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800040000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2 2	Accessories (individual part or installation kit)										
Mounting rail TS 32 9821006000 Mounting rail (secured on central bosses C/D) 9810009000 External mounting brackets 980202000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800040000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2 2	Mounting plate	9512187000									
Mounting rail TS 35 9822008000 Earthing rail (secured on central bosses C/D) 9810009000 External mounting brackets 980202000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800040000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2 2	Mounting rail TS 15	-									
Earthing rail (secured on central bosses C/D) External mounting brackets 9802022000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 9800040000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2 2	Mounting rail TS 32	9821006000									
External mounting brackets 980202000 External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800040000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2 2	Mounting rail TS 35	9822008000									
External articulated hinges** 9802025000 Internal articulated hinges, flexible, for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 9800040000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2 2	Earthing rail (secured on central bosses C/D)	9810009000									
Internal articulated hinges, flexible, for enclosure with quick-release fastener Silicone seal for extended temperature range (by the metre) Mounting bushes with 4 screws M3 x 8 9800040000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2 2	External mounting brackets	9802002000									
for enclosure with quick-release fastener 9801076000 Silicone seal for extended temperature range (by the metre) on request Mounting bushes with 4 screws M3 x 8 9800040000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2 2	External articulated hinges**	9802025000									
Silicone seal for extended temperature range (by the metre)	Internal articulated hinges, flexible,										
Mounting bushes with 4 screws M3 x 8 9800040000 Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2 2	for enclosure with quick-release fastener	9801076000									
Maximum possible number of threads ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2 2	Silicone seal for extended temperature range (by the metre)	on request									
ISO M 12 16 20 25 32 40 50 63 Side A/B 38 16 12 8 4 2 2 2	Mounting bushes with 4 screws M3 x 8	9800040000									
Side A/B 38 16 12 8 4 2 2 2	Maximum possible number of threads										
	ISO M 12 16 20 25 32 40 50 63										
Side C/D 17 8 5 3 2 2 1 0	Side A/B 38 16 12 8 4 2 2 2										
	Side C/D 17 8 5 3 2 2 1 0										
** Enclosure preparation required	** Enclosure preparation required										




250 x 160 x 120 mm

CT-911 Polycarbonate enclosures CT-912 ABS enclosures

B SCOVER F COVER F 250 244/243 * 227/226 * A B 190.5 212 238

360 x 200 x 150 mm

CT-881 Polycarbonate enclosures CT-882 ABS enclosures



^{*} Smaller dimension at mounting plate support

Туре	CT-911 PC	CT-912 ABS								
Weight (g)	830 (PC)	660 (ABS)								
External dimension (mm)	250 x 160 x	120								
Ordering data Enclosure (painted) with seal (PUR)	Part numb	er								
PC, with quick-release fastener	29100000	00								
PC, with screw fastener	291000100	00								
PC, with transparent cover (PC) and quick-release fastener	291100000	00								
ABS, with quick-release fastener	39100000	00								
ABS, with screw fastener	391000100	00								
ABS, with transparent cover (PC) and quick-release fastener	391100000	00								
Accessories (individual part or installation kit)										
Mounting plate	95121870	00								
Mounting rail TS 15	-									
Mounting rail TS 32	9821006000									
Mounting rail TS 35	98220080	00								
Earthing rail (secured on central bosses C/D)	981000900	00								
External mounting brackets	98020020	00								
External articulated hinges**	980202500	00								
Internal articulated hinges, flexible,										
for enclosure with quick-release fastener	980108000	00								
Silicone seal for extended temperature range (by the metre)	on request									
Mounting bushes with 4 screws M3 x 8	980004000	00								
Maximum possible number of threads										
ISO M 12 16 20 25 32 40 50 63										
Side A/B 38 16 12 8 4 2 2 2										
Side C/D 17 8 5 3 2 2 1 0										
** Enclosure preparation required										

^{*} Smaller dimension at mounting plate support

Weight (g) 1550 (PC) 1375 (ABS ABS ABS ABS ABS ABS ABS ABS ABS ABS										
External dimension (mm) 260 x 200 x 150 27 Part number 28 P										
Prince Prince Prince (PC) with seal (PUR) Part number PC, with quick-release fastener PC, with screw fastener PC, with transparent cover (PC) and quick-release fastener PC (PC) and quick-release fastener PC (PC) and quick-release fastener										
PC, with quick-release fastener 288000000 PC, with screw fastener 2880001000 PC, with transparent cover (PC) and quick-release fastener 2881000000										
PC, with screw fastener 2880001000 PC, with transparent cover (PC) and quick-release fastener 2881000000										
PC, with transparent cover (PC) and quick-release fastener 2881000000										
ABS, with quick-release fastener 3880000000										
ABS, with screw fastener 3880001000										
ABS, with transparent cover (PC) and quick-release fastener 3881000000										
Accessories (individual part or installation kit)										
Mounting plate 9512020000										
Mounting rail TS 15 –										
Mounting rail TS 32 9821013000										
Mounting rail TS 35 9822016000										
Earthing rail (secured on central bosses C/D) 9810034000										
external mounting brackets –										
external articulated hinges** 9802026000										
nternal articulated hinges, flexible,										
or enclosure with quick-release fastener –										
Silicone seal for extended temperature range (by the metre) on request										
Mounting bushes with 4 screws M3 x 8 9800026000 (M4 x 8)										
Maximum possible number of threads										
SO M 12 16 20 25 32 40 50 63										
Side A/B 70 32 24 16 10 6 4 4										
Side C/D 26 11 8 5 3 2 2 1										
* Enclosure preparation required										


300 x 230 x 86 mm

CT-871 Polycarbonate enclosures CT-872 ABS enclosures

(COVER) (COVER

300 x 230 x 110 mm

CT-891 Polycarbonate enclosures CT-892 ABS enclosures



^{*} Smaller dimension at mounting plate support

Smaller and		,,, uc		9	piace	зарр	OIC					
Туре										CT-871 PC	CT-872 ABS	
Weight (g)	3 (3)										850 (ABS)	
External dim	external dimension (mm)									300 x 230 x	86	
Ordering data Enclosure (painted) with seal (PUR)										Part numb	er	
PC, with quid	ck-rel	ease	faster	ner						28700000	00	
PC, with scre	w fas	tene	r							28700010	00	
PC, with tran	spare	ent co	over (l	PC) ar	nd qu	ick-re	lease	fastene	er	28710000	00	
ABS, with qu	ıick-re	elease	e faste	ener						38700000	00	
ABS, with sc	rew fa	sten	er							38700010	00	
ABS, with tra	anspa	rent	cover	(PC) a	and q	uick-r	releas	e faster	ner	38710000	00	
Accessories (individual part or installation kit)											,	
Mounting pl	ate									95120190	00	
Mounting ra	il TS 1	5								_		
Mounting ra	il TS 3	2								98210100	00	
Mounting ra	il TS 3	5								98220130	00	
Earthing rail	(secu	red c	n cen	tral b	osses	C/D)				9810012000		
External mou	unting	g bra	ckets							98020020	00	
External artic	culate	d hir	iges*	+						98020250	00	
Internal artic	ulate	d hin	ges, f	lexibl	e,							
for enclosure	with	quic	k-rele	ase fa	asten	er				98010790	00	
Silicone seal	for ex	tend	led te	mper	ature	range	e (by	the me	tre)	_		
Mounting bu	ushes	with	4 scre	ews N	13 x 8					98000250	00	
Maximum p	ossib	le nu	ımbe	r of t	hread	ds						
ISO M	12	16	20	25	32	40	50	63				
Side A/B	34	14	10	6	4	0	0	0				
Side C/D	21	13	5	4	2	0	0	0				
** Enclosure	prepa	aratio	n req	uired								

^{*} Smaller dimension at mounting plate support

Туре										CT-891 PC	CT-892 ABS	
Weight (g)										1155 (PC)	1000 (ABS)	
External dim	ensio	n (mn	n)							300 x 230 x	(110	
Ordering da	ta En	Part numb	er									
PC, with quick-release fastener										28900000	00	
PC, with scre	w fast	tener								28900010	00	
PC, with tran	spare	nt co	ver (P	C) an	d qui	ck-rel	ease	fastene	er	28910000	00	
ABS, with qu	ick-re	lease	faste	ner						38900000	00	
ABS, with sci	ew fa	stene	er							38900010	00	
ABS, with tra	nspar	ent c	over ((PC) a	nd qı	uick-re	elease	e fastei	ner	38910000	00	
Accessories	(indiv	idual	part	or ins	tallat	ion ki	t)					
Mounting pla	ate									9512019000		
Mounting ra	ITS 1	5								-		
Mounting ra	ITS 32	2								98210100	00	
Mounting ra	ITS 3	5								98220130	00	
Earthing rail	(secur	red oi	n cent	tral bo	osses	C/D)				98100120	00	
External mou	ınting	brac	kets							9802002000		
External artic	ulate	d hin	ges**							98020250	00	
Internal artic	ulated	d hing	ges, fl	exible	2,							
for enclosure	with	quick	c-relea	ase fa	stene	r				98010820	00	
Silicone seal	for ex	tende	ed ter	npera	ture	range	(by t	he me	tre)	-		
Mounting bu	shes	with 4	4 scre	ws M	3 x 8					98000250	00	
Maximum p	ossib	le nu	mbei	of th	read	s						
ISO M	12	16	20	25	32	40	50	63				
Side A/B	34	14	10	6	4	0	0	0				
Side C/D	21	13	5	4	2	0	0	0				
** Enclosure	prepa	ratio	n requ	uired								
							-					